

FASCIA

BULLNOSE 180mm x 25mm



BULLNOSE 210mm x 30mm




BULLNOSE 230mm x 30mm




BOARDS


DAR - D4SRC depth - 18mm



DAR - D4SRC depth - 30mm



DAR - D4SRC depth - 42mm



DAR - D4SQ depth - 30mm x 11mm



DAR - D4SQ depth - 42mm x 11mm



DAR - D4SQ depth - 66mm x 11mm



DAR - D4SQ depth - 90mm x 11mm



DAR - ????? depth - 18mm x 18mm



DAR - ????? depth - 30mm x 18mm



DAR - ????? depth - 42mm x 18mm




DAR - ????? depth - 66mm x 18mm



DAR - ????? depth - 90mm x 18mm



DAR - ????? depth - 116mm x 18mm



DAR - ????? depth - 138mm x 18mm



DAR - ????? depth - 185mm x 25mm



HAND RAILS, MIDDLE RAILS & BOTTOM RAILS

BOTTOM RAIL BR? 66mm x 30mm



BOTTOM RAIL BR? 66mm x 42mm



BOTTOM RAIL 66mm x 42mm



BOTTOM RAIL 62mm x 18mm

to be drawn

MIDDLE RAIL BR? 66mm x 42mm

Middle rail to be drawn

MIDDLE RAIL BR? 66mm x 42mm

Middle rail to be drawn

MIDDLE RAIL BR? 42mm x 30mm

Middle rail to be drawn

MIDDLE RAIL BR? 42mm x 42mm

Middle rail to be drawn

HAND RAIL HR1 DR 66mm x 66mm



HAND RAIL HR? DR 66mm x 66mm

Bread loaf rails to be drawn

HAND RAIL HR5 88mm x 42mm



HAND RAIL HR1 DR 66mm x 66mm



HAND RAIL HR? DR 66mm x 66mm

Bread loaf rails to be drawn

HAND RAIL HR5 138mm x 42mm

Board rail to be drawn

DOOR JAMBS

SINGLE 138mm x 30mm



DOUBLE 138mm x 30mm



SINGLE 163mm x 30mm



DOUBLE 163mm x 30mm



CLADDING

WEATHERBOARD CLASSIC REBATED BEVELBACK 138mm x 18mm



WEATHERBOARD CLASSIC REBATED BEVELBACK 185mm x 18mm



WEATHERBOARD RUSTICATED 185mm x 19mm



WEATHERBOARD RUSTICATED 138mm x 19mm



BEAMS

GL8 140mm x 65mm



GL8 180mm x 65mm



GL8 240mm x 65mm



GL8 280mm x 65mm




POSTS

GL8 2mm Round Corners 88mm x 88mm



GL8 2mm Round Corners 112mm x 112mm



GL8 2mm Round Corners 135mm x 135mm



MOULDINGS

QUAD 18mm



QUAD 23mm



EXTERNAL CORNER MOULD 42mm x 42mm



SCOTIA 30mm x 30mm



Why choose Jenkin Tru-Pine?

- ✓ Strong and durable
- ✓ H3 Hazard Class protection
- ✓ Pre-primed
- ✓ Defect free
- ✓ Strict quality control
- ✓ Proven history
- ✓ Plantation pine

Premium quality timber ideal for above ground, outdoor use, structurally graded, smooth, dressed finish for easy painting. Available in an extensive range of sizes. The perfect finish for your outdoor living.



POSTS, BEAMS
& CLADDING



HAND RAILS, BALUSTRADES,
POSTS & BOARDS

USAGE

Jenkin Tru-Pine is a premium exterior treated timber for above ground use only. Ensure a timber clearance of 100mm above paved surfaces or 175mm above finished ground level is maintained.

TREATMENT

Jenkin Tru-Pine achieves a H3 Hazard Class protection rating through treatment with an advanced organic treatment using LOSP (Light Organic Solvent Preservative) that protects against fungal decay and insect attack.

FIXINGS

Use hot-dip galvanised nails, screws, bolts and brackets in general locations. For coastal conditions subject to sea spray use stainless steel.

SEALING

During the installation process all exposed unprimed surfaces resulting from cut ends, mitres, notching, boring, punched nail holes or similar should be resealed with a suitable acrylic or oil-based premium exterior timber primer.

PAINTING SPECIFICATION

1. Spot prime and putty all nail holes.
2. Ensure primed surfaces are clean and free from contaminants such as dust, grease or mildew.
3. Apply a minimum of two full coats of premium acrylic exterior house paint to recommended film thickness

For a better finish and extended paint durability we recommend the application of one full coat of premium quality OIL BASED primer undercoat.

Use colours that have a Light Reflective Value (LRV) of 45 to 100 (100 being pure white). Colours with a LRV of 44 to 0 (0 being pure black) progressively generate extreme surface heat when exposed to direct sunlight and can cause resin bleed, shrinkage, distortion and cracking. It will also reduce the service life of the paint coatings.

STORAGE

Store the product in a dry environment away from damp ground until use. Kiln-dried Radiata Pine timber is hygroscopic and will absorb moisture in a damp environment and release it in a dry environment. If timber absorbs moisture, some dimensional swelling will occur.

HEALTH & SAFETY

Jenkin Tru-Pine treated products are safe to handle using normal timber handling precautions.

TECHNICAL DATA & INSTALLATION GUIDE

Please refer to the Building Code of Australia guidelines or your local building authority/council to ensure correct construction practices are followed.

Jenkin Tru-Pine meets Service Class 3/AS5068 standards for structural products.

Visit www.jenkin.co.nz for technical specifications, product information guides, span tables, application guides and warranties.

Jenkin
Tru-Pine